



Weighing Technology

*A Higher Level of Precision...A Higher Level of Performance*

**FS/FS2**  
SERIES

## **Stainless Steel Washdown Bench & Platform Scale**

- Large 2 Inch Backlit Display
- FS2 with Hermetically Sealed Load Cell and All Stainless Base



*Manufactured by an ISO 9001 certified company.*



Model	FS-60 / FS2-60K	FS-150 / FS2-150K	FS-300 / FS2-300K
Capacity	60 kg / 132 lb	150 kg / 330 lb	300 kg / 660 lb
Readability	0.01 kg / 0.02 lb / 0.5 oz	0.02 kg / 0.05 lb / 1 oz	0.05 kg / 0.1 lb / 2 oz
Divisions	6,000	7,500	6,000
Weighing Units / Functions	kg, lb, lb : oz		
Stabalization Time (seconds)	< 1.5		
Tare Range	To capacity by subtraction		
Power Source	Built-in rechargeable battery or external power adapter (included)		
Construction	Stainless steel platform, pillar, indicator and housing (Aluminum load receiving structure on FS models / All stainless steel base and hermetically sealed load cell on FS2 models)		
Display	2 inch / 51 mm wide viewing angle backlit LCD		
Pan Size (W x D x H)	16.7 x 20.7 x 4.5 inches / 425 x 525 x 120 mm		
Dimensions (W x D x H)	16.7 x 20.7 x 36.8 inches / 425 x 525 x 935 mm		
Operating Environment	32° ~ 104° F non condensing R.H. ≤ 85%		
Net Weight	48.4 lb / 22 kg		
Shipping Weight	50 lb / 22.3 kg		
NEMA/IP Rating	FS Series - NEMA 4X / IP 65 / FS2 Series - NEMA 4X / IP 68		
Options	Stainless steel wheel kit		

### FS / FS2 Series



### Features

- All stainless steel housing and pan
- Heavy duty construction
- Sealed electronics. Waterproof tactile keypad
- Low profile
- Large LCD display with wide angle viewing and backlight
- Extendable pillar (another 5.5 inches / 140 mm)
- Reads in kilograms, pounds and pounds : ounces
- Built-in rechargeable battery or external power adaptor
- Accumulation function
- Zero tracking
- Automatic power save
- Low battery indicator
- Auto-calibration function
- Adjustable stainless steel feet with rubber inserts
- Indicator rotates through 135 degrees
- Gravitational correction software (FS2 models only)

### Benefits

- Easy to clean for food processing or harsh environments
- Will withstand harsh industrial operation
- Improved water and dust resistance
- Easy to load and unload platform only 4.7 inches / 120 mm high
- Easy to see weight values from a distance, reduces mistakes
- Enables bulky objects to be weighed
- Flexibility of operation
- Portability - battery lasts a minimum of 120 hours (without back light)
- Allows you to add together consecutive weights to arrive at a total
- Assures that you always start weighing at zero
- Conserves battery power
- Alerts you to charge the battery, saving downtime
- Ensures accuracy
- Scale remains level for accurate results on uneven working surfaces - anti-slip
- Enables viewing from all angles
- Enables you to input different G acceleration factors